



### Main

Product or component type	Surge protection device
Range of product	Square D

### Complementary

Surge current	40 kA per phase
System Voltage	600Y/347 V AC
Phase	3 phases
Wiring configuration	4-wire
[Uc] maximum continuous operating voltage	510 V
Nominal discharge current	10 kA
Short-circuit protection	200 kA
Local signalling	Status LED, green = normal operation
Height	3 in
Width	3.6 in
Depth	3.4 in

### Environment

NEMA degree of protection	NEMA 4X
enclosure material	Plastic, colour : black
standards	CSA C22.2 No 8 UL 1449 type I ed. 4 NEC 285 type I
ambient air temperature for operation	149 °F (65 °C)

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1640 - Schneider Electric declaration of conformity	Compliant - since 1640 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
DINP which is known to the State of California to cause cancer and	DINP which is known to the State of California to cause cancer and
DIDP which is known to the State of California to cause birth defects or other reproductive harm.	DIDP which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.